Belinea

[Belinea 10 15 80]

The multifaceted 15-inch display for entering the TFT world.

The Belinea 10 15 80 expands the Belinea portfolio from MAXDATA with a multifaceted 15-inch display.

Not only does this display include integrated speakers, but height adjustability and a 90° rotation feature are part of the package as well. The space-saving design, flawless ergonomics, as well as the outstanding value for the money, make this display the ideal partner for the office or home-office environment.
And it goes without saying that this flexible entry-level display model has TCO03 and ISO13406-2 certifications.

D-Sub connection for analogue graphic cards

Lift function and pivot preparation for flexibility

Belinea 10 15 80 – The multifaceted 15-inch

- 15 inch (38.1 cm)
- analogue
- Sound, Lift,90° turnable
- Viewing angle: 130° / 110°
- Response time rise / fall: 5 / 20 ms

Target Groups

- **Small and Medium Business**
- **Price sensitive users**

MAXDATA Computer GmbH & Co. KG • Elbestraße 12-16 • D-45768 Marl • www.maxdata.de

08/2004 ® Errors and omissions exempt.

MAXDATA
REAL HARD WARE

Belinea 10 15 80 - Technical Data

Panel characteristics

Image size	15“
Viewable image size in inch / cm	15“ / 38.1
Max. picture size (w x h) in mm	304.1 x 228.1
Physical resolution	1024 x 768
Pixel pitch in mm	0.297 x 0.297
Active Matrix, TFT	•
Panel technology	TN
Displayable colours (max.)	16.2 Mio (FRC)
Brightness in cd / qm	250
Contrast ratio	300:1
Viewing angle horizontal	130°
Viewing angle vertical	110°
Coating	Anti Glare
Response time: rise / fall in ms	5 / 20
Backlight	4 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 60
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	80
Input voltage 110-230V, 50-60 Hz	•
Power consumption in Watt (On / Sleep)	40 / 1
Input signal (VGA-card) analog / digital	• / –
Output audio amplifier	2 x 2 Watt

Features

Factory / user defined modes	8 / 9
OSD	•
Integrated microphone	–
Integrated speaker	•
Lift / Pivot	60 mm / •
Power supply in the panel /in the stand / external	• / – / –
Tilt back / forth	20° / 3°
Swivel right / left	– / –
Colour	ClassicGrey

Controls

Brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	• / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	– / •
Zoom / frequency	– / •
Recall / video signal selection	• / –
OSD position / OSD language(s)	• / 10
Mute	–
Volume	•

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	–
1280 x 1024	–

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / •
TCO99	•
TÜV GS /TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc.to VESA standard	–
MAC compliant	•

Connections

15-pin Mini-D-Sub	•
24-pin DVI-D	–
Headphone plug	•
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect.15-pin Mini-D-Sub / 24-pin DVI-D (opt.)	•
Audio cable	–
Optional accessories	•
Microphone cable	–
Pivot software	• (Mod. 30 90 20)

Physical specification

Size (w x h x d) in mm	346 x 402 x 201
Net / gross weight in kg	3.8 / 5

Warranty

3 years incl. Panel and Backlight	•

Austria
MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux
MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal
MAXDATA Iberia
Edificio Prisma • C/ Colquide, 6
28230 – Las Rozas (Madrid)

France
MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY-LISSES

Germany
MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45768 Marl

Italy
MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland
MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Puławska 303
02-785 Warszawa

Switzerland
MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom
MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: